

Levaflex

PVC REINFORCED FLEXIBLE HOSES



Catalog No.	Internal Diameter Diamètre Nominal		General Purpose Transparent green Color				Heavy Duty Silver Grey Color			
	Inch - Pouce		Weight Poids Gr./M	Wall Thickness Epaisseur de la paroi mm	Bursting Pressure Pression d'éclatement Kp/cm ²	Bending Radius Rayon minimal de courbure mm	Weight Poids Gr./M	Wall Thickness Epaisseur de la paroi mm	Bursting Pressure Pression d'éclatement Kp/cm ²	Bending Radius Rayon minimal de courbure mm
012	1/2	Inch	190	2.7	30	55	330	4.6	40	100
058	5/8	Inch.	225	3.2	29	60				
034	3/4	Inch	300	3.5	26	75	470	4.6	40	140
100	1	Inch	400	3.7	24	120	600	4.6	40	160
114	1 1/4	Inch.	500	3.8	21	150	700	4.8	30	200
112	1 1/2	Inch.	625	4.0	19	170	800	5.0	30	230
200	2	Inch.	900	4.2	16	220	1200	5.6	25	300
212	2 1/2	Inch.	1150	4.6	15	290	1650	6.0	25	370
300	3	Inch.	1500	5.0	13	350	2000	6.2	20	450
312	3 1/2	Inch	1800	5.2	13	430	2500	6.6	15	550
400	4	Inch.	2180	5.8	12	480	3300	7.2	15	630
500	5	Inch.					4200	8.3	15	850
600	6	Inch.	4300	7.3	10	810	6300	9.8	10	1100
800	8	Inch.					10300	12.0	10	1850

- *Technical Data are subject to ±5%.*
- *Les Données Techniques sont sujettes à ±5%.*

